



# OPUS LUBRICANTS PRODUCT DATA

## SYNOPUS MAX FE 10W/30 LOW SAPS

### Description

**SYNOPUS MAX FE 10W/30 LOW SAPS** is a very high spec heavy duty diesel engine oil that is designed to meet the necessary chemical limits required to maintain the efficiency of exhaust after-treatment devices, especially DPF's and SCR, EGR NOX reduction systems.

**SYNOPUS MAX FE 10W/30 LOW SAPS** provides the highest level of rationalisation in mixed fleets where a number of manufacturers, models and engines are being used. The Low Saps additive technology coupled with synthetic base oils also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

### Applications

**SYNOPUS MAX FE 10W/30 LOW SAPS** is designed to allow fleet operators to run their new vehicles to maximum oil drain intervals. Its primary application is for the latest low emission Euro V and VI European trucks and buses, especially those requiring a Low SAPS lubricant.

### Performance Levels

- ACEA: E4/E7/E8/E11-22
- API: CK-4
- MB: 228.31 / 228.51 228.52
- MAN M3777 / M3677 / M3775 / M3477 / M3271-1
- MTU Type 3.1 / Type 2.1
- Deutz DQC IV-18 LA
- VOLVO VDS 4.5
- RLD-4 / RLD-3
- SCANIA LDF- 4
- EOS – 4.5
- Caterpillar ECF-3
- Cummins CES 20086 / CES 20081
- DH-2-17, DH-1-17, DL-0-17
- Detroit Diesel 93K218, 93K222
- DAF PSQL 2.1E-LD

### Benefits

- Maximum oil drain intervals.
- The unique Low SAPS additive system keeps on working even in the toughest conditions.
- Efficient after-treatment systems. Maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation.
- Engine protection. Designed to protect the latest European vehicles against all types of engine wear, deposit and soot build-up and bore-polishing. The unique formulation continues to protect under the most severe conditions, thus extending engine life.



### Typical Data

<b>SAE</b>		<b>10W/30</b>
Specific Gravity	@ 15°C cSt	0.853
Kinematic Viscosity	@ 100°C cSt	11.80
	@ 40°C cSt	67.0
Viscosity Index		174
Total Base Number		10.0
Pour Point ™C		-40
Flash Point ™C		220
Sulphated Ash		<1.0

Revision Date: July 2024

**Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW**

**Tel: 0141 445 3555**

**E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)**

**Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)**