



OPUS LUBRICANTS PRODUCT DATA

STOU 10W/40

Description

This is a multipurpose tractor oil meeting all the requirements of the mechanical components of the major manufacturers including 'wet' brakes, hydraulics, gears and transmissions.

The product is developed and tested for the most arduous duties of modern agricultural machinery with the additive package not only approved against the world's two major STOU specifications, Ford and Massey Ferguson, but is also acknowledged by other leading manufacturers.

Performance Levels

John Deere: J27 & J20C*
Massey Ferguson CMS M1139, M1144, M1145
Allison C4
API: GL4
Ford M2C 159 B
ZF TE-ML 06A, 06B, 06C, 06D, 07B
Caterpillar TO-2
API: CE, CF, CF-4, CG-4, SF
ACEA E2
MB: 228.1, 228.3
MAN 271
MIL-L-2104D

Benefits

- Multigrade and multifunctional.
- Rationalisation of grades.
- Additive package giving excellent oxidation and thermal stability.
- Anti-'squawk'.

Typical Data

SAE		10W/40
Specific Gravity	@ 15°C cSt	0.870
Kinematic Viscosity	@ 100°C cSt	14.51
	@ 40°C cSt	100
Viscosity Index		152
Pour Point (°C)		-37
TBN (mg KOH/gram)		11.6

Revision Date: March 2023