



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS NOVA 10W/60

Description

A premium fully synthetic engine oil with special protective additives for ultimate level of engine protection that exceeds USA and European industry standards.

Recommended for all petrol engines (multi-valve and turbo types, with or without catalytic converter) and all diesel engines, turbo-charged or naturally aspirated in cars and light vans.

Designed to provide protection under severe driving style or conditions.

Stability and endurance under extreme conditions (heat, load, speed) that can cause conventional oils to break down.

Performance Levels

- API: SN/CF
- ACEA A3/B3, A4/B4
- MB 229.1
- VW 501.00 / 505.00
- PSA B71 2300

Benefits

- Ensures maximum protection under all operating conditions.
- Exceptional protection at high and low temperatures.
- Synthetic technology ensures minimum piston deposits, low oil consumption and maximum exhaust catalyst efficiency.

Technical Data

SAE		10W/60
Specific Gravity	@ 15°C cSt	0.871
Kinematic Viscosity	@ 100°C cSt	24.2
	@ 40° C cSt	161
Viscosity Index		179
Flash Point (COC °C)		200
Ash, Sulphated:		1.1
Pour Point °C		-49

Revision Date: December 2021

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW

Tel: 0141 445 3555

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk