



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS NOVA C2 & C3 5W/30

Description

Synopsis Nova C2 & C3 5W/30 is a Mid SAPS (Sulphated Ash, Phosphorus and Sulphur) fully synthetic engine oil formulated with latest additive technology for use in both modern Euro 4 & 5 compliant petrol and diesel engines with or without Diesel Particulate Filters (DPF).

Application

Synopsis Nova C2 & C3 5W/30 provides a high level of component protection and cleanliness for standard and long drain intervals in a wide range of passenger cars and light commercial vehicles as specified by the manufacturer.

Benefits

- Improved Fuel Economy.
- Excellent Colds Starting Characteristics.
- Very High Viscosity Index.
- Improved Thermal Stability & Engine Cleanliness.
- Low Volatility.

Performance

- ACEA: C2 & C3-21
- API: SN / CF
- BME LL-04
- MB: 229.51, 229.31, 229.5
- GM: DEXOS 2
- RN0700 / 0710

Typical Properties

Specific Gravity @ 15°C cSt:	0.85
Kinematic Viscosity @ 100°C cSt:	10.60
Kinematic Viscosity @ 40°C cSt:	60.80
Viscosity Index:	165
Flash Point (COC °C):	220
Pour Point °C:	-36
Sulphated Ash	<0.8

Revision Date: October 2024

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW

Tel: 0141 445 3555

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk