



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS NOVA MLS 5W/30

Description

Synopsis Nova MLS 5W/30 Mid SAPS (Sulphated Ash, Phosphorus, Sulphur) fully synthetic based multigrade engine oil is formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils for petrol and diesel engine applications.

Synopsis Nova MLS 5W/30 has been developed for use in Euro 4 and 5 compliant vehicles with or without diesel particulate filters (DPF)

The additive technology coupled with synthetic base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals. It is a long-life engine oil which meets the following requirements:

Performance Levels

- API: SN/CF
- ACEA: C3
- MB 229.31 / 229.51 / 229.52
- BMW Longlife - 04
- GM DEXOS 2
- RN 0700 (Pending)

Benefits

- Improved fuel economy.
- Low volatility.
- Very high viscosity index.
- Excellent cold starting characteristics.
- Better thermal stability, improved engine cleanliness.

Technical Data

SAE		5W/30
Specific Gravity	@ 15°C cSt	0.849
Kinematic Viscosity	@ 100°C cSt	11.80
	@ 40° C cSt	70.00
Viscosity Index		160
Flash Point (COC °C)		220
Pour Point °C		-36

Revision Date: May 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk