



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS NOVA MLS 5W/40

Description

Synopsis Nova MLS 5W/40 is a synthetic multigrade engine oil manufactured using high quality additives and base oils for fuel efficiency and superior performance for petrol and diesel engines of modern passenger cars and light commercial vehicles.

The additive technology coupled with synthetic base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals. It is a long-life engine oil which meets the following requirements:

Performance Levels

- API: SN/CF
- ACEA: C3
- MB 229.31 / 226.5
- BMW LL-04
- VW 502.00 / 505.01
- PORSCHE – A40
- FORD WSS – M2C917A (Capable)
- RN 0700 / 0710
- GM DEXOS 2

Benefits

- Improved fuel economy.
- Low volatility.
- Very high viscosity index.
- Excellent cold starting characteristics.

Better thermal stability, improved engine cleanliness

Technical Data

SAE		5W/40
Specific Gravity	@ 15°C cSt	0.853
Kinematic Viscosity	@ 100°C cSt	13.70
	@ 40° C cSt	81.00
Viscosity Index		174
Flash Point (COC °C)		220
Pour Point °C		-36

Revision Date: May 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk