



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS NOVA VLS 5W/30

Description

Synopsis Nova VLS 5W/30 Mid SAPS (Sulphated Ash, Phosphorus, Sulphur) fully synthetic based multigrade engine oil is formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils for petrol and diesel engine applications.

Synopsis Nova VLS 5W/30 has been developed for use in Euro 4 and 5 compliant vehicles with or without diesel particulate filters (DPF)

The additive technology coupled with synthetic base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals. It is a long-life engine oil which meets the following requirements:

Performance Levels

- ACEA: C3
- API: SN
- MB 229.51
- BMW Longlife 04
- VW 504.00/507.00
- PORSCHE C30

Benefits

- Improved fuel economy.
- Low volatility.
- Very high viscosity index.
- Excellent cold starting characteristics.
- Better thermal stability, improved engine cleanliness.

Technical Data

SAE		5W/30
Specific Gravity	@ 15°C cSt	0.854
Kinematic Viscosity	@ 100°C cSt	10.00
	@ 40°C cSt	58.00
Viscosity Index		160
Flash Point (COC °C)		220
Pour Point °C		-36

Revision Date: April 2020

Ferguson & Menzies Ltd

312 Broomloan Road

GLASGOW

G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk