



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

OPUS GEAR OIL 75W/90 GL5

Revision 0

Revision date 2017-02-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	OPUS GEAR OIL 75W/90 GL5
--------------	--------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC24] Lubricants, greases, release products;
-------------	---

1.3. Details of the supplier of the safety data sheet

Company	Ferguson & Menzies Ltd
Address	312 Broomloan Road Glasgow G51 2JW
Web	www.fergusonmenzies.co.uk
Telephone	0141-445 3555
Fax	0141-425 1079
Email	info@fergusonmenzies.co.uk
Email address of the competent person	info@fergusonmenzies.co.uk

1.4. Emergency telephone number

Emergency telephone number	0141-445-3555 09.00 - 17.00
----------------------------	--------------------------------

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
SULPHURISED ISOBUTYLENE			270-943-2		1 - 10%	R52/53	

OPUS GEAR OIL 75W/90 GL5

Revision 0

Revision date 2017-02-17

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Solvent Neutral 500							
SULPHURISED ISOBUTYLENE			270-943-2				
Solvent Neutral 150		64741-88-4	265-090-8				
acrylic copolymer							
ALKYL PHOSPHORIC ACID ESTER AMINE SALTS Nexbase 3060		72623-87-1	276-738-4				
Solvent Neutral 100							
DIBUTYL HYDROGEN PHOSPHITE POLYBUTENYL SUCCINIMIDE			217-316-1				
ALKYLATED TALLOW AMINE			263-186-4				
Long chain alkenyl amine			204-015-5			Acute Tox. 4: H302; Skin Corr. 1B: H314; Eye Dam. 1: H318; STOT SE 3: H335; STOT RE 2: H373; Aquatic Acute 1: H400; Carc. 1B: H350;	
Baseoil - unspecified - lubricating oils (petroleum), C15-30, hydrotreated neutral oil-base	649-482-00-X	72623-86-0	276-737-9				

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

OPUS GEAR OIL 75W/90 GL5

Revision 0

Revision date 2017-02-17

6.4. Reference to other sections

See section 8 for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

7.3. Specific end use(s)

See section 1.2 for further information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Adopt best Manual Handling considerations when handling, carrying and dispensing.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear protective clothing.

Eye / face protection

In case of splashing, wear:.. Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Colour	Brown
Odour	Characteristic
Initial boiling point	>200°C
Flash point	>180°C
Relative density	0.875 - 0.900
Description	Liquid
Water solubility	Immiscible in water

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Heat, sparks and open flames.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

Do not breathe gas/fumes/vapour/spray.

OPUS GEAR OIL 75W/90 GL5

Revision 0

Revision date 2017-02-17

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
	No data is available on this product.

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

Further information

	No data is available on this product.
--	---------------------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

Disposal methods

	Contact a licensed waste disposal company.
--	--

Disposal of packaging

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
--	--

OPUS GEAR OIL 75W/90 GL5

Revision 0

Revision date 2017-02-17

SECTION 16: Other information**Other information**

Text of risk phrases in Section 3	R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Text of Hazard Statements in Section 3	<p>Acute Tox. 4: H302 - Harmful if swallowed.</p> <p>Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.</p> <p>Eye Dam. 1: H318 - Causes serious eye damage.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .</p> <p>Aquatic Acute 1: H400 - Very toxic to aquatic life.</p> <p>Carc. 1B: H350 - May cause cancer .</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---