



OPUS LUBRICANTS PRODUCT DATA

B RANGE ENGINE OILS

Description

OPUS B Engine Oils are a range of cost-effective low detergent automotive oils manufactured from quality refined base oils designed for all petrol engines, but only for diesel engines that are naturally aspirated. These oils can be used in older vehicles requiring the type of oil with cannister filtration (not gauzed type).

Performance Levels

- API: CC/SE
- MIL-L-2104B
- CCM2C-90014A
- MIL-L-46152B

Benefits

Excellent value petrol and diesel engine oils where turbo charged requirements are not necessary.

Typical Data

SAE		10W	SAE 20	10W/30	10W/40	20W/20
Specific Gravity	@ 15°C:	0.871	0.863	0.875	0.869	0.880
Kinematic Viscosity	@ 100°C cSt:	5.4	7.7	10.4	14.10	8.6
Pour Point (°C)		-22	-22	-36	-34	-18
Flash Point (°C)		200	210	200	210	200

SAE		20W/30	15W/40	30	40	50
Specific Gravity	@ 15°C:	0.875	0.890	0.885	0.890	0.90
Kinematic Viscosity	@ 100°C cSt:	10.4	13.6	10.0	13.6	17.4
Pour Point (°C)		-28	-36	-18	-18	-18
Flash Point (°C)		200	200	200	200	200

Revision Date: June 2021

Ferguson & Menzies Ltd
312 Broomloan Road
Glasgow
G51 2JW

Tel: 0141 445 3555
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk