



OPUS LUBRICANTS PRODUCT DATA

D ENGINE OILS 10W; SAE 20; 20W/20; SAE 30; SAE 40; SAE 50

Description

OPUS D Engine Oils are manufactured from high quality base oils and additives and are suitable for use in normally aspirated and turbo charged diesel and petrol engines in passenger cars, light and heavy commercials, plant, compressor, industrial and certain hydraulic and transmission applications.

Performance Levels

- API: CD/SF
- Allison: C-3
- MIL-L-2104D
- Caterpillar: TO-2
- MIL-L-46152C
- CCMC: G2/D2

Benefits

Excellent value oils with all round performance, meeting the latest CCMC 'shear stability' requirements. Economic mixed fleet applications.

Typical Data

SAE		D 10W	SAE 20	20W/20	SAE 30	SAE 40	SAE 50
Specific Gravity	@ 15°C	0.861	0.863	0.864	0.870	0.872	0.880
Kinematic Viscosity	@ 100°C cSt	5.6	7.7	7.4	10.4	14.2	17.4
	@ 40°C cSt	31.2	51.3	52.0	83.0	120.0	170.0
Pour Point (°C)		-25	-22	-22	-20	-20	-18
Flash Point (°C)		200	210	210	225	225	225
Viscosity Index		119	115	103	108	118	110
TBN (mg KOH/gram)		5.10	5.14	5.14	5.10	5.08	5.10

Revision Date: August 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk