



# OPUS CONSTRUCTION PRODUCT DATA

## EASYSTRIKE S

### **Description**

Opus Easystrike S is an Eco friendly ready to use quality cream emulsion of water in oil. It was originally intended for use on absorbent formwork surfaces, especially timber. Modern chemical technology however has provided Opus Easystrike S with properties also suited to use on most types of formwork surfaces, including steel, but protection against weathering should be considered on any sealed surface.

This highly cost effective product is non-staining, pleasant to use, gives reduction in blow holes and is an excellent preservative for untreated timber moulds. For pre-treatment of new timber moulds it is recommended to apply two coats of Opus Easystrike S before use to increase 'form life'.

### **Advantages**

- Affects a clean positive release, reducing labour costs, cleaning time and possible damage to formwork.
- Assists production of stain free, quality concrete finish.
- Protects timber forms against ingress of moisture, extending their useful life.
- A water based product, therefore non-flammable.
- Supplied ready for use; economically and easily applied.
- User friendly product.

### **Properties**

|                   |  |
|-------------------|--|
| Appearance:       | Creamy white liquid  |
| Specific Gravity: | 0.970 @ 15°C   |
| Flash Point:      | Non-flammable  |
| EEC Labeling:     | Non-harmful' classification as the product formulation is based on highly refined oils |
| Freezing Point:   | 0°C  |
| Storage Life:     | Indefinite in manufacturer's sealed drums  |

### **Application**

Apply Opus Easystrike S by brush, squeegee or mop. The latest formulation allows the Product to be also spray applied. Please refer to Ferguson Menzies Technical Department for specific details.



### **Coverage**

10-20 m<sup>2</sup>/litre dependent on surface porosity, profile, methods of application and air temperature.

|                   |       |                          |
|-------------------|-------|--------------------------|
| Untreated plywood | ..... | 10 m <sup>2</sup> /litre |
| Treated plywood   | }     |                          |
| Plastics          | }     | 20 m <sup>2</sup> /litre |
| Steel             | }     |                          |

### **Storage & Handling**

Opus Easystrike S is supplied in manufacturer's sealed drums and requires no special storage facilities.

Protect from frost.

Slight agitation required after storage, prior to application.

### **Packaging**

Opus Easystrike S is supplied in 205 litre drums and 20 litre containers.

These materials do not constitute a health hazard and do not promote a dermatitic or carcinogenic reaction provided reasonable care is exercised according to Health and Safety Regulations.

Revision Date: June 2016

**Ferguson & Menzies Ltd**  
**312 Broomloan Road**  
**GLASGOW**  
**G51 2JW**

**Tel: 0141 445 3555**

**Fax: 0141 425 1079**

**E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)**

**Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)**