



OPUS LUBRICANTS PRODUCT DATA

EXTRA-X 10W/40

Description

OPUS EXTRA-X 10W/40 is an extremely high performance mixed fleet diesel and petrol engine oil, formulated for operators demanding extended oil drain intervals of up to 100,000 km.

Applications

OPUS EXTRA-X 10W/40 is recommended for a wide range of diesel engines requiring a lubricant with the performance level ACEA E7 including commercial vehicles, buses, agricultural, construction and plant equipment.

Performance Levels

API: CI-4 / SL

ACEA: E7

Detroit Diesel DD 93K215

Caterpillar: ECF-1a, ECF-2

Cummins: CES 20076/7/8

MAN: 3275

Volvo: VDS-3

Mercedes-Benz: 228.3

Mack: EO-N

MTU Type 2

Renault RVI, RLD-2

Benefits

Fulfills the requirements of the EU Euro 4 emission standards for Trucks & Buses.

Suitable for SCR systems, not for DPF.

Long-life maximises engine durability.

Extended intervals between oil changes, up to 100,000 kms

Improved performance under all conditions

Increased engine protection and low volatility.

Typical Data

SAE		10W/40
Specific Gravity	@ 15°C	0.879
Kinematic Viscosity	@ 100°C cSt	13.40
	@ 40°C cSt	90.0
Viscosity Index		150
Sulphated Ash, wt %		1.38
Pour Point °C		-35
Flash Point (COC °C)		200
TBN (mg KOH/gram)		10.5



Revision Date: May 2015

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk