



OPUS LUBRICANTS PRODUCT DATA

FAME-X 10W/40

Description

FAME X 10W/40 is a semi-synthetic engine oil manufactured using high quality additives and group 3 base oils, it is an extremely high performance long life diesel engine oil. The additive technology coupled with group 3 base oils also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

Applications

FAME X 10W/40 has a wide range of applications including OEM's such as Volvo, Mercedes, DAF and MAN. It is also suitable for many buses, tractors and off highway applications.

Performance Levels

- API: CI4/SL
- ACEA: E7
- Caterpillar: ECF-1a
- MAN: 3275
- Cummins: CES 20076/7/8
- Volvo: VDS-3
- Mercedes-Benz: 228.3
- Mack: EO-N
- MTU Type II

Benefits

- Extended intervals between oil changes.
- Improved performance under all conditions.
- Increased engine protection and low volatility
- Excellent cold starting.
- Improved oil consumption and emissions.

Typical Data

SAE		10W/40
Specific Gravity	@ 15°C	0.866
Kinematic Viscosity	@ 100°C cSt	14.50
	@ 40°C cSt	100.0
Viscosity Index		152
Pour Point °C		-30
Flash Point COC (°C)		220
TBN (mg KOH/gram)		10.2

Revision Date: July 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk