



OPUS LUBRICANTS PRODUCT DATA

GREEN LITHIUM COMPLEX EP2 EXTRA

Description

A specially developed multi-purpose lithium complex grease for lubricating all anti-friction and plain bearings for use in industrial and automotive applications. The grease has shown exceptional performance providing extended lubrication intervals over wide operating temperature range.

Features

- Exceptional mechanical stability extends relubrication intervals
- Excellent oxidation stability provides lasting lubrication at high temperatures
- Excellent EP and anti-wear performance
- Good corrosion resistance protects components operating in wet conditions

Application

Green Lithium Complex EP2 Extra can be applied manually, or by using a standard grease gun (400gm cartridges available), or via a central lubricating system designed for and capable of pumping an NLGI No.2 grease; consult a qualified centralised lubrication systems engineer before installation.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

Typical Physical Properties

Appearance	-	Smooth Extra Tacky grease
Colour	-	Green
NLGI Classification	-	2
Thickener	-	Lithium Complex
Base Oil	-	Solvent refined mineral oil
Base oil viscosity @ 40°C (IP71) cSt	-	150 min
Worked penetration (IP50)	-	265 to 295
Dropping point (IP132) °C	-	260 min.
Oil separation (IP121) %	-	5 max.
Copper corrosion (IP112)	-	Pass
Resistance to corrosion EMCOR (IP220)	-	0 : 0
Water washout (IP215) @ 38°C %	-	3
@ 79°C %	-	4



Typical Physical Properties ctd

Four Ball Weld Load (IP239) kgs	-	400
Wear load index	-	62
Timken OK load (IP326) kgs (lbs)	-	20 (45)
Operating temperature range:	-	- 20°C to + 150°C

The content of this data sheet is given in good faith but without warranty.

Revision Date: June 2020

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk