



# OPUS LUBRICANTS PRODUCT DATA

## HT PLUS 10W-30

### Description

**Opus HT Plus 10-30** is a multifunctional transmission and hydraulic fluid for tractors and plant. For use in transmission and final drives and suitable for wet brakes, hydraulic and power steering.

### Performance Levels

- API: GL4
- Massey Ferguson: M-1135, M-1141, M1143, M1145
- New Holland: NH420A, NH410B
- Ford: M2C134D, M2C86B, C
- Case International: MS-1204,6,7,9
- Allison: C4
- Caterpillar: TO-2
- Volvo WB101
- John Deere J20C
- ZF TE ML: 03E, 05F, 06E, 06F, 06K, 06N, 06R, 17E, 21E
- Dennison: HF-0, HF-1, HF-2

### Benefits

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

### Typical Data

SAE		10W-30
Specific Gravity	@ 15°C	0.866
Kinematic Viscosity	@ 100°C cSt	10.50
	@ 40°C cSt	66.80
Viscosity Index		145
Pour Point °C		-37°C

Revision Date: January 2025

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW

Tel: 0141 445 3555

E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)

Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)