



# OPUS LUBRICANTS PRODUCT DATA

## LIMITED SLIP 85W/90 GEAR OIL GL5

### Description

**OPUS Limited Slip 85W/90** is an extra high performance, automotive gear lubricant formulated from select base oils and an advanced additive system specifically for limited-slip differentials. This lubricant is recommended for use in applications requiring API GL-5 performance such as heavy duty differentials, axles, and final drives where extreme pressures and shock loading are expected.

### Applications

- Limited Slip differential, axles and final drives requiring API GL5 level performance.
- Passenger cars, on highway light and heavy duty trucks, buses and vans.
- Off highway industries including: construction, quarrying and agriculture.
- Other industrial and automotive applications involving hypoid and other gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque conditions prevail.
- Initial fill, top up and refill of enclosed automotive type gearing where 85W/90 Limited Slip Gear Lubricants are recommended.
- Not intended for transmissions or transaxles for which engine oil or automatic transmission fluids are recommended.

### Performance Levels

OPUS Limited Slip 85W/90 meets or exceeds the requirements of the following industry and builder specifications:

- API GL-5
- ZF TE-ML 05C/12C/16E

## **Benefits**

Today's truck and automotive equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, heavier loads, and limited-slip capability require improved formulations to maximise differential life and optimise performance. Longer service intervals place additional demands on the gear lubricant. OPUS Limited Slip 85W/90 Gear Lubricant is engineered to meet these challenges. The key benefits include:

- Excellent frictional properties.
- Effective limited-slip performance.
- Good thermal stability and resistance to high temperature oxidation.
- Extended gear and bearing life due to minimal deposits and longer seal life.
- Protects against low speed/high torque wear and against high speed scoring Increased load carrying capability reducing operating costs.
- Excellent rust, staining, and corrosion protection.
- Reduced wear and maintenance costs.
- Effective low temperature lubrication Reduced wear and ease of start-up.
- Good resistance to foaming.
- Maintains film strength for reduced wear.
- Compatible with typical automotive seals and gaskets.
- Minimum leakage and reduced contamination

<b><u>Typical Data</u></b>		<b>85W/90</b>
Specific Gravity	@ 15°C	0.889
Kinematic Viscosity	@ 40°C cSt	153.0
	@ 100°C cSt	15.3
Viscosity Index		100
Pour Point °C		-30
Flash Point COC (°C)		216

Revision Date: September 2016

**Ferguson & Menzies Ltd**  
**312 Broomloan Road**  
**GLASGOW**  
**G51 2JW**

**Tel:** 0141 445 3555  
**Fax:** 0141 425 1079  
**E-Mail:** [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
**Web:** [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)