



# OPUS LUBRICANTS PRODUCT DATA

## LITHIUM 000 EP GREASE

### Description

A premium quality grease prepared from refined base oils and lithium hydroxy stearate soap thickener. The grease contains soil soluble EP additives to provide protection against seizure under highly loaded service conditions. The grease also contains additives to inhibit oxidation and rust. It is particularly suited for use in industrial equipment and in some automotive gear box applications. It is easily pumped over long distances, even at low temperatures.

### Typical Properties

Appearance:	Smooth fluid grease
Colour:	Dark Brown
Worked Penetration (IP50):	445 – 475
NLGI Classification:	000
Timken OK Load (IP326):	45 lbs
Dropping Point (IP132):	140° C
Operating Temperature Range:	-30 to +110° C
4 Ball (IP239) Weld Load:	315 kg
Mean Hertz Load:	58
Copper Corrosion (IP112):	1b

Revision Date: March 2018

**Ferguson & Menzies Ltd**  
**312 Broomloan Road**  
**GLASGOW**  
**G51 2JW**

**Tel:** 0141 445 3555  
**Fax:** 0141 425 1079  
**E-Mail:** [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
**Web:** [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)