



# OPUS LUBRICANTS PRODUCT DATA

## ROCKDRILL OIL ISO 150

### Description

Rockdrill Oil ISO 150 is an extreme pressure treated rock drill and pneumatic lubricant, designed for use in rock drills, jack hammers and other similar air operated tools.

On pneumatic tools, due to the expansion of air, the temperature may be considerably lower than ambient. Rockdrill Oil is formulated to be free flowing through airline lubricators and integral oilers under these conditions.

### Benefits

- Excellent load carrying properties
- Superior corrosion protection
- Contains tackiness agents to help oil adhere to working parts

### Typical Data

Appearance:		Amber liquid
Specific Gravity	@ 15.5°C	0.889
Kinematic Viscosity	@ 40°C cSt	150.00
Flash Point (COC°C)		220

### Storage

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Revision Date: September 2016

**Ferguson & Menzies Ltd**  
**312 Broomloan Road**  
**GLASGOW**  
**G51 2JW**

**Tel:** 0141 445 3555  
**Fax:** 0141 425 1079  
**E-Mail:** [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
**Web:** [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)