



OPUS LUBRICANTS PRODUCT DATA

STOU 15W/40

Description

OPUS STOU 15W/40 is a multipurpose tractor oil manufactured from high quality base oils and additives meeting all the requirements of the mechanical components of the major manufacturers including 'wet' brakes, hydraulics, gears and transmissions.

The product is developed and tested for the most arduous duties of modern agricultural machinery with the additive package against the world's two major STOU specifications, Ford and Massey Ferguson, but is also acknowledged by other leading manufacturers.

Performance Levels

John Deere: J27 & J20C*

Massey Ferguson CMS M1139, M1144, M1145

Allison C4

API: GL4

Ford M2C 159 B

ZF TE-ML 06A, 06B, 06C, 06D, 07B

Caterpillar TO-2

API: CE, CF, CF-4, CG-4, SF

ACEA E2

MB: 228.1, 228.3

MAN 271

MIL-L-2104D

Benefits

- Multigrade and multifunctional.
- Rationalisation of grades.
- Additive package giving excellent oxidation and thermal stability.
- Excellent low-temperature flow characteristics, providing superior cold-start protection.
- Anti-'squawk'.
- Enhanced gear wear protection.
- Advanced hydraulic pump performance.



Typical Data

SAE		15W/40
Specific Gravity	@ 15°C cSt	0.886
Kinematic Viscosity	@ 100°C cSt	13.5
	@ 40°C cSt	99.0
Viscosity Index		136
Pour Point (°C)		-39
Flash Point (COC°C)		195
TBN (mg KOH/gram)		10.7

Revision Date: October 2021

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW
Tel: 0141 445 3555 E-Mail: info@fergusonmenzies.co.uk Web: www.fergusonmenzies.co.uk