



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS HT PLUS 0W/30

Description

SYNOPSIS HT-PLUS 0W/30 is a multifunctional Hydraulic/Transmission Oil (UTTO) for Tractor Transmissions and Plant engineered to meet the tough demands of heavy-duty, hydraulic-powered farm and commercial equipment. The Synthetic base stocks and additives effectively reduces wear, resists heat, protects against rust and extends fluid and equipment service life. Synopsis HT-Plus 0W/30 Hydraulic/Transmission Oil is recommended for extended oil drain intervals based on an oil analysis program.

Performance Levels

- API GL-4
- VOLVO WB 102 (97304), WB 101 (97303)
- JOHN DEERE J20D, J20C, J20B, J20A
- MASSEY FERGUSON M1145, M1143, M1141, M1135
- CASE NEW HOLLAND MAT 3540, MAT 3526, MAT 3525, MAT 3505
- CASE MS 1206, MS 1207, MS 1209, MS 1210,
- NEW HOLLAND NH 420A, NH 410B
- ZF TE-ML 03E, 05F, 06K, 17E
- KUBOTA SUPER UDT, UDT
- VALTRA G2-10
- ALLISON C-4
- CATERPILLAR TO-2
- FORD M2C134-D, M2C86-B
- KOMATSU AXO80

Benefits

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

Typical Data

SAE	0W/30
Specific Gravity @ 15°C	0.862
Kinematic Viscosity @ 100°C cSt	9.50
@ 40°C cSt	54.00
Viscosity Index	175
Flash Point °C	228
Pour Point °C	-50
Cold-Crank Simulator -35°C	6200
Brookfield Viscosity @ -40°C	22000

Revision Date: February 2024

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW

Tel: 0141 445 3555

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk