

# **OPUS LUBRICANTS PRODUCT DATA**

## **SYNOPUS HT PLUS 5W/30**

#### Description

**SYNOPUS HT-PLUS 5W/30** is a multifunctional Hydraulic/Transmission Oil (UTTO) for Tractor Transmissions and Plant engineered to meet the tough demands of heavy-duty, hydraulic-powered farm and commercial equipment. The Synthetic base stocks and additives effectively reduces wear, resists heat, protects against rust and extends fluid and equipment service life. Synopus HT-Plus 5W/30 Hydraulic/Transmission Oil is recommended for extended oil drain intervals based on an oil analysis program.

#### **Performance Levels**

John Deere: J20C & J20DFord: M2C134D, M2C86B,C

 Case International: MS1204,1206,1207,1209

• CNH MAT3526

• New Holland: NH420A, NH410B

 Massey Ferguson: M1135,M1141,M1143,M1145 Volvo WB 101, 97303

ZF TE ML 03E/05F/06E/06F/06K/17E/21E

Valtra G2-10Allison: C4Caterpillar: TO-2

• API: GL-4

• Denison: HF-0,HF-1,HF-2

• Sperry Vickers/Eaton: I-280-S & M2950S

#### **Benefits**

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

### **Typical Data**

SAE		5W/30
Specific Gravity @ 15°C		0.855
Kinematic Viscosity	@ 100°C cSt	10.10
	@ 40°C cSt	55.40
Viscosity Index		171
Flash Point <sup>o</sup> C		228
Pour Point <sup>o</sup> C		-48
Cold-Crank Simulator -30ºC		6600
Brookfield Viscosity @ -35°C		13900

March 2022