



OPUS LUBRICANTS PRODUCT DATA

SYNOPUS MAX 10W/40

Description

SYNOPUS MAX 10W/40 is a superior heavy duty diesel engine oil manufactured using high quality additives and base oils. The additive technology coupled with synthetic base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals. **SYNOPUS MAX 10W/40** is recommended for highly rated diesel engines meeting Euro 1, Euro II, Euro III, Euro IV and Euro V emission requirements. It is suitable for engines without particulate filters, and for most EGR engines fitted with SCR NOx reduction systems.

Applications

SYNOPUS MAX 10W/40 is recommended for commercial vehicles, buses, trucks, plant and agricultural equipment.

Performance Levels

- API: CI-4/SL
- ACEA: E4 / E7
- MB 228.3
- MAN 3275
- VOLVO VDS - 3
- Cummins CES 20076/77/78
- Caterpillar ECF-2

Benefits

- Long drain benefits with 100,000 km between oil changes.
- Reduced fuel consumption.
- Low volatility.
- Improved soot control.
- Very high viscosity index.

Technical Data

		10W/40
Specific Gravity	@ 15°C cSt	0.870
Kinematic Viscosity	@ 100°C cSt	14.50
	@ 40°C cSt	95.00
Viscosity Index		154
Flash Point (COC °C)		220
Pour Point °C		-36
TBN		12.40

Revision Date: December 2021

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW
Tel: 0141 445 3555 E-Mail: info@fergusonmenzies.co.uk Web: www.fergusonmenzies.co.uk