



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS TWO STROKE OIL

Description

Synopus Two Stroke is a specially formulated, fully synthetic, ashless high performance two stroke oil. Synopus Two Stroke utilises the latest additive technology along with a balanced combination of synthetic base stocks in order to meet the complex and severe demands laid down by JASO.

Benefits

- Ultra low smoke formulation
- Highly durable formulation
- Protection against piston and cylinder scuffing
- Prevents pre-ignition and power loss by reducing unwanted combustion chamber deposits
- Reduces exhaust blockage contaminants
- High film strength for ultimate engine protection

Applications

Synopus Two Stroke is principally designed for use in medium to high output motorcycles but can be used in a variety of other two stroke applications such as mopeds, motor scooters and chainsaws. It is suitable for pre-mix and oil injection systems.

Always refer to the vehicle/equipment handbook for mixing ratios.

Product Specification

- API: TC
- JASO: FD
- ISO: EGD

Typical Data

Appearance	Red
Specific Gravity @ 15.6°C	0.870
Kinematic Viscosity @ 100°C, cSt	8.1
Flash Point, °C	140



Health & Safety

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Revision Date: August 2017

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk